

# DULUX<sup>®</sup> AUTOSOLV<sup>®</sup> 482-S2598 LACQUER CLEAR COAT SPRAYPAK



Dulux Australia  
ABN 67 000 049 427

## Product Name:

482-S2598 Dulux<sup>®</sup> Autosolv<sup>®</sup> Lacquer Clear coat Spraypak

## Product Description:

Dulux<sup>®</sup> Autosolv<sup>®</sup> Lacquer Clear coat Spraypak is a premium quality acrylic clear coat. It produces a high gloss flexible film with excellent durability and adhesion. Dulux<sup>®</sup> Autosolv<sup>®</sup> Lacquer Clear coat Spraypak should be applied over Dulux<sup>®</sup> Autosolv<sup>®</sup> Lacquer colour, 428 line or Dulux<sup>®</sup> AutoSpeed<sup>®</sup> PT basecoat, 440 line.



Refer to Technical Data sheet for Dulux<sup>®</sup> Autospeed<sup>®</sup> PT Tinters, 440 Line and Dulux<sup>®</sup> Autosolv<sup>®</sup> Lacquer tinters, 482 line.

## Application guide:

**Before spraying:** Shake can for at least 2 minutes or until the mixing ball rattles inside the can. For best results, avoid spraying in low temperatures (less than 15°C) or high humidity.

**During spraying:** Hold the can upright 20-25 cm from the surface. To ensure compatibility, test spray on an inconspicuous area. Use smooth, even strokes parallel to the surface. Apply several light mist coats rather than 1 heavy coat to avoid runs and sags.

**After spraying:** Prevent blocking by turning can upside down and spraying until clear gas emerges. Wipe the nozzle clean. Clean up overspray while still wet with Dulux<sup>®</sup> General purpose thinner.

|   |                    |                                   |
|---|--------------------|-----------------------------------|
|   | <b>Application</b> | Apply 2-3 even coats              |
|  | <b>Air Flash</b>   | 5 minutes air flash between coats |
|   | <b>Touch dry</b>   | 10 minutes                        |
|   | <b>Recoat</b>      | After 1 hour                      |
|  | <b>Drying</b>      | 60 mins @ 25°C                    |

## For Safe Handling:

**DULUX<sup>®</sup>**  
**AUTOSOLV<sup>®</sup>**  
**482-S2598 LACQUER CLEAR**  
**COAT SPRAYPAK**



Dulux Australia  
ABN 67 000 049 427

---

Please refer to the Material Safety Data Sheet No: 22216 for this product before use.  
**In the event of an emergency contact: 1 800 033 111 (ALL HOURS)**

**For further information contact:**

|                   |   |
|-------------------|---|
|                   | Dulux Australia                           |
|                   | 1956 Princes Hwy, Clayton, Victoria, 3168 |
|                   | Australia                                 |
|                   | ABN 67 000 049 427                        |
| <b>Telephone:</b> | 1 800 810 114                             |
| <b>Fax:</b>       | 61 3 9314 0596                            |

Dulux, AutoSolv and Autospeed are registered trademarks. Marks followed by the symbol <sup>™</sup> are trademarks.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by Dulux Refinish Coatings in relation to goods manufactured by it or their use and application is given in good faith and is believed by Dulux Refinish Coatings to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Dulux Refinish Coatings provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Dulux Refinish Coatings by any condition or warranty implied by applicable legislation, regulation or other Government ordinance voiding or prohibiting such exclusion, limitation or modification