PRODUCT SOLUTIONS



AUTOMOTIVE

COATINGS

Dulux[®]

FLEETSHIELD

ULTRAEPOXY[®] 2K PRIMER

EASY SANDING VHIGHER PRODUCTIVITY

LIGHT GREY

488S0088 4L



Worth doing, worth Dulux*

Fleetshield UltraEpoxy 2K Epoxy Primer

Dulux FleetShield™ UltraEpoxy is a premium, easy sanding 2K Epoxy Primer.

Due to the faster dry times compared to FleetShield Ultrabuild, UltraEpoxy streamlines workflow, improving productivity and efficiency.

It can be used as a wet-on-wet or sandable primer, gives excellent adhesion to metal substrates and provides anti-corrosive properties.

UltraEpoxy can be air dried or cured at lower temperatures providing lower energy use.

Features:

- ✓ Easy Sanding
- ✓ Higher Productivity
- ✓ Excellent Adhesion



Product	Size	Product Code
FleetShield UltraEpoxy Part A - Light Grey	4L	488S0088-4L
FleetShield UltraEpoxy Part B	1L	980S0089-1L



Fleetshield UltraEpoxy Technical Data

Suitable Substrates	Sound existing finishes Steel 316 grade stainless steel Aluminium and galvanized surfaces Fibreglass ABS plastic Polyester filler		
Additives	Part A Dulux [®] FleetShield UltraEpoxy Primer Pt A - 488S0088 Part B Dulux [®] FleetShield Ultra Epoxy Primer Pt B - 980S0089 Thinners Dulux [®] 2K Thinner Normal - 92089292 Dulux [®] 2K RP Thinner - 92089819 Dulux [®] 2K Thinner Slow - 92089847 Dulux [®] Cold Cure Thinner - 920S0063		
Mixing Ratio	Part A - 4 Parts UltraEpoxy Part A by volume Part B - 1 Part UltraEpoxy Part B by volume Thinner - 10-20% by volume		
Spray Viscosity	Ford 4 Cup - 30 seconds at 20% thinning		
Gravity & Suction Feed	Fluid Tip: Conventional: 1.4 – 1.8mm	Spraying Pressure: 350-450 kPa. Or refer to manufacturer's recommendations	
Pressure Pot	Conventional: 1.1 – 1.8mm	Spraying Pressure: 350-450 kPa. Or refer to manufacturer's recommendations	
Application	1 to 2 even coats for a dry film build of 60-80 micron		
Air Flash	10 - 15 minutes air flash between coats at 25°C		
Baking/Drying	8 hours at 25°C 40 mins at 50°C		

Refer to full TDS for further details | duluxautomotive.com



AUTOMOTIVE COATINGS

Contact

Dulux[®] Auto Refinish Coatings customer service team is available for all advice, technical and colour assistance. call: **1800 810 114** or visit: **duluxautomotive.com**

Office

Dulux® Auto Refinish Coatings 1–15 Pound Road West Dandenong South VIC 3175